



NEW VULCAIN RANGE

A DURABLE SOLUTION FOR THE MOST EXTREME ENVIRONMENTS



enjoy safety.

f @ y in
www.deltaplus.eu

NEW VULCAIN RANGE

The perfect solution for extreme environments, where robustness and durability are key.



RUBBER SOLE

Fluid drainage channel

To avoid trapping dust and liquids

Propulsion zone

Extra grip at the front
SR: +15% compared with standard EN ISO 20345:2022

Ladder crampons

Complies with the new LG standard

Wide, high crampons

Particularly suitable for unstable terrain

Shock absorption zone

PERFORMANCE

The sole: solid and stable

- ▶ HRO rubber outsole (300°C for 60 seconds)
- ▶ Slip resistance test (SR): +15% vs EN ISO 20345:2022
- ▶ Ladder grip: complies with the new LG standard
- ▶ Width and height of studs adapted to the most unstable terrain
- ▶ Anti-puncture sole (PS test carried out with a 3mm insert): +38.5% vs EN ISO 20345:2022

DURABILITY

WPA full-grain nubuck leather :

- ▶ Tear resistance: +26% vs EN ISO 20345:2022
- ▶ Cut resistance: +45% vs EN ISO 20345:2022

Comfort :

- ▶ Scuff Cap (SC): reinforced toe protection against abrasion
- ▶ HI (heat insulation) : +19% vs EN ISO 20345:2022
- ▶ CI (cold insulation) : +33% vs EN ISO 20345:2022

TECHNOLOGY

Anti-twist system :

Allows the foot to fit perfectly inside the shoe, preventing lateral torsion.

- ① Optimum heel support
- ② Additional lateral tightening
- ③ Precise fit



COLIMA S3S SR

38 ▶ 48

Robust and comfortable high-cut shoe, adapted to more difficult environments.

Upper : Leather - Nubuck | Lining : Mesh | Insole : PU - Synthetic - Foam | Outsole : Injected - PU - 2d - Nitrile rubber | Anti-perforation insert : Metal free | Safety toe-cap : Composite | Lacing system : Laces | Weight : 780 g per shoe

EN ISO 20345
S3S FO HI CI
HRO CR SC LG SR



ARENAL S3S SR

38 ▶ 48

Robust and comfortable low-cut shoe, adapted to more difficult environments.

Upper : Leather - Nubuck | Lining : Mesh | Insole : PU - Synthetic - Foam | Outsole : Injected - PU - Nitrile rubber | Anti-perforation insert : Metal free | Safety toe-cap : Composite | Lacing system : Laces | Weight : 730 g per shoe

EN ISO 20345
S3S FO HI CI
HRO SC LG SR

