

# ProVest II™

Prolar™ padding in the upper chest area and shoulder to protect the sawyer from dangerous chain saw kickbacks.









### ProVest II™

Ideal for loggers, DOT and DPW workers, utility workers, arborists, and landscapers.

### **Product Features:**

- Multi-layered Prolar™ padding protects the upper chest and shoulders from kickbacks.
- ProVest II™ uses the same Prolar™ pads as our proven chain saw chaps, which are and certified to ASTM-1897-2008.
- Prolar™ fibers "explode" on contact to jam a running chain saw.
- ProVest II™ has added numerous pockets to provide functionality and convenience.
- Sleeveless vest, with mesh back and open sides keep the sawyer cool in hot, humid conditions.
- Outer fabric is water-resistant, breathable 65/35 poly-cotton blend.
- Can be worn over most heavy coats.

### Other Key Product Features

- Lightweight, cool and comfortable.
- Open sides with adjustable straps provide a wide range of adjustability to fit either thin or wide girths and with/without coats.
- Includes numerous pockets on the inside and out.
- Available in high visibility orange/blue.

### WASHING INSTRUCTIONS:

Wash by hand or in a washing machine on the gentle cycle using cold water and mild detergent. DO NOT use any bleach or harsh detergents as they can damage the fibers of the garment's protective pads. Hang to dry. DO NOT dry using a hot dryer.

WARNING!! Improper washing or drying will damage and reduce the protective features of the protective pads and may result in serious injury or death!

## **Ordering Information**

Product No.	Product Description
JE-70SM	ProVest II™, Water Resistant, 65/35 Poly-Cotton Blend, Orange, Small, 36" - 38"
JE-70M	ProVest II™, Water Resistant, 65/35 Poly-Cotton Blend, Orange, Medium, 38" - 42"
JE-70L	ProVest II™, Water Resistant, 65/35 Poly-Cotton Blend, Orange, Large, 42" - 46"
JE-70XL	ProVest II™, Water Resistant, 65/35 Poly-Cotton Blend, Orange, X-Large, 46" - 52"

### A WARNING to USER

Elvex® ProVest™ II is designed with protective padding in the upper chest and shoulder areas. THE PROTECTIVE PADDING IN THIS GARMENT MEETS THE CHAIN SAW CUT RESISTANCE TEST OF ASTM F1414-04. This protective garment is designed to reduce the risk of injury to the body parts covered by the protective padding if contacted by a rotating saw chain. THIS GARMENT PROVIDES LIMITED PROTECTION AND MAY NOT PREVENT PENETRATION OF THE SAW CHAIN AND WILL NOT PREVENT ALL INJURIES, but may give the wearer extra time to react and thereby prevent or reduce the severity of injury.

This garment must be properly fitted and all garment fasteners must be used and snugly adjusted on the wearer. An unfastened or loosely fitted garment provides little or no protection. The protective garment must be worn at all times when operating a chain saw.

This garment is not intended to be a substitute for good chain saw operating practices. Carefully read and follow all safety and maintenance instructions in your current Chain Saw and Saw Chain Owner's or Safety Manual. The garment must be immediately replaced it is damaged, improperly washed, cut, sewn, patched or otherwise modified or repaired.

FAILURE TO FOLLOW ALL OF THE ABOVE WARNINGS AND INSTRUCTIONS MAY RESULT IN SERIOUS PERSONAL **INJURY INCLUDING DEATH!** 

